

TRANCE 2 (GE)



SPECS

TELAIO	
TAGLIE	XS, S, M, L, XL
COLORAZIONI	Metallic Black/ Black / Iris, Metallic Green / Metallic Black
TELAIO	ALUXX SL-Grade Aluminum 140mm Maestro Suspension
FORCELLA	Fox 34 Rhythm, 150mm travel, GRIP2 Damper, Boost 15x110mm QR, tapered steerer
AMMORTIZZATORE	Fox Float DPS Performance, trunnion mount
COMPONENTISTICA	
MANUBRIO	Giant Connect Trail, 780x31.8mm
ATTACCO MANUBRIO	Giant Connect
TUBOSELLA	Giant Contact Switch dropper post with remote lever, 30.9mm
SELLA	Giant Contact (neutral)
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano SLX, 2x11 M7000, I-Spec 11 2x11
DERAGLIATORE	Shimano SLX R7025-D
CAMBIO	Shadow Deore XT, Shadow+ M8000 GS Shadow+
FRENI	Shimano BR-MT520 [F] 180mm [R] 180mm, hydraulic disc
COMANDI FRENO	Shimano BL-MT501
PACCO PIGNONI	Shimano SLX, M7000 11x42
CATENA	KMC X11-1
GUARNITURA	Shimano SLX M7000 Boost, 26/36 con MRP 2x CS Guide
RUOTE	
DROP MOVIMENTO CENTRALE	Shimano Press Fit
CERCHI	Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width
MOZZI	[F] Giant Tracker Performance Boost 15x110mm, sealed bearing [R] Giant Tracker Performance, Boost 12x148, sealed bearing
RAGGI	Sapim
COPERTURE	[F] Maxxis high Roller II 27.5x2.5 WT, 60 tpi, EXO, TR [R] Maxxis high Roller II 27.5x2.4, 60 tpi, EXO, TR, tubeless

CARATTERISTICHE

- Telaio: ALUXX SL-Grade Aluminum 140mm Maestro Suspension
- Forcella: Fox 34 Rhythm, 150mm travel, GRIP2 Damper, Boost 15x110mm QR, tapered steerer
- Leve del cambio: Shimano SLX, 2x11 M7000, I-Spec 11 2x11
- Guarnitura: Shimano SLX M7000 Boost, 26/36 con MRP 2x CS Guide
- Colorazioni: Metallic Black/ Black / Iris, Metallic Green / Metallic Black

Prezzo: € 2.399

GEOMETRIA

TELAIO	XS	S	M	L	XL
Lunghezza tubo sella (mm)	370	380	431	482	507
Angolo tubo sella	73,5°	73,5°	73,5°	73,5°	73,5°
Lunghezza tubo orizzontale (mm)	560	580	610	630	655
Lunghezza tubo sterzo (mm)	100	100	105	130	145
Angolo sterzo	67,0°	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	42	42	42	42	42
Trail (mm)	104	104	104	104	104
Interasse (mm)	1109	1129	1160	1183	1209
Lunghezza carro posteriore (mm)	435	435	435	435	435
Drop movimento centrale (mm)	15	15	15	15	15
Stack (mm)	587	587	591	614	628
Reach (mm)	386	406	435	448	469
Altezza stand over (mm)	697	701	723	768	788
Larghezza manubrio c/c (mm)	780	780	780	780	780
Lunghezza attacco manubrio (mm)	40	50	50	50	60
Larghezza pedivella (mm)	170	170	175	175	175
Dimensione ruote	27.5"	27.5"	27.5"	27.5"	27.5"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso.